

Clear-Com offer a versatile range of headsets, handsets and Microphones that are designed to give excellent audio quality, comfort and ease of use to suit every need. Our range of headsets can be used with all Clear-Com Party-line and Matrix products as well as wired and wireless belt packs.

Headsets

CC-260

The CC-260 is a double ear enclosed durable and professional headset that offers full range audio response and great comfort. The CC-260 includes an enclosed ear design with leatherette cushion to reduce background noise and provide excellent acoustic isolation. The boom microphone is equipped with a noise cancelling mic element and 270 degree rotation for left or right side use. A range of replacement parts are available to support the CC-260. For more information please contact your local Clear-Com representative.

CC-95

The CC-95 is a single ear enclosed headset that offers the same full range audio response, acoustic isolation, comfort and durability as the CC-260. The 270 degrees boom rotation offers the user the option of left or right ear operation. A range of replacement parts are available to support the CC-95. Please contact your local Clear-Com Representative.

CC-40 & CC-60

The CC40 and CC-60 are single or double enclosed ear general purpose intercom headsets with flexible neck microphones that are ideal for minor adjustments. The headsets offer a durable design with comfort and excellent audio isolation. A range of replacement parts are available to support these headsets. Please contact your local Clear-Com Representative.

CC-25

The CC-25 is a super light weight headset with electret microphone. The microphone is only available with mini Jack plug for use only on 600 Series belt packs.

CC-26K

The CC-26K is a single open ear, lightweight headset with an over-the-head design. The dynamic noise cancelling microphone improves voice clarity and flexible neck boom.

CC-27

The CC-27 is a contemporary design, single-ear, wrap around ear worn headset. The dynamic noise cancellation microphone offers excellent frequency response and accurate voice pick-up. This headset offers great comfort during prolonged use.



CC-260



CC-95



CC-40



CC-60



CC-27



CC-25



CC-26K

Headsets Comparison Chart

Headset Model	Ear Headset Type	Connector Type (Cable End)	Ear phone Type	Weight Type	Earpad Type	Microphone Type	Impedance (Ohms) Mic / Earpiece
CC-260	Double	XLR (f) 4 Pin	Enclosed	399g	Leatherette	Dynamic	220 / 220
CC-260-6	Double	XLR (f) 6 Pin	Enclosed	399g	Leatherette	Dynamic	220 / 220
CC-260-R	Double	XLR (m) 4 Pin (RTS Compatible)	Enclosed	399g	Leatherette	Dynamic	220 / 220
CC-260-X5	Double	XLR (m) 5 Pin	Enclosed	399g	Leatherette	Dynamic	220 / 220
CC-95	Single	XLR (f) 4 Pin	Enclosed	282g	Leatherette	Dynamic	220 / 420
CC-95-R	Single	XLR (m) 4 Pin (RTS Compatible)	Enclosed	282g	Leatherette	Dynamic	220 / 420
CC-95-X5	Single	XLR (m) 5 Pin	Enclosed	282g	Leatherette	Dynamic	220 / 420
CC-60	Double	XLR (f) 4 Pin	Enclosed	390g	Leatherette	Dynamic	200 / 200
CC-40	Single	XLR (f) 4 Pin	Enclosed	265g	Leatherette	Dynamic	200 / 400
CC-26K-X4	Single	XLR (f) 4 Pin	Open	39g	Foam	Dynamic	200 / 400
CC-26K-DIN	Single	DIN (m) 5 Pin	Open	39g	Foam	Dynamic	200 / 400
CC-26K-X5	Single	XLR (m) 5 Pin	Open	39g	Foam	Dynamic	200 / 400
CC-27	Single	XLR (f) 4 Pin	Open	30g	Foam	Dynamic	200 / 90
CC-25	Single	2.5mm Jack	Open	25g	Foam	Electret	2200 / 32
HS-6	Handset	XLR (f) 4 Pin	Open	330g	N/A	Dynamic	800 / 200
PT-7	Push-to-talk Mic	XLR (f) 4 Pin	Mic only	165g	N/A	Dynamic	640 / -

Handsets

PT-7 Hand-held mic

A rugged, push-to-talk hand-held microphone with mounting clip. 1.5m/5 ft coil cord with 4 pin female XLR connector.

HS-6 Telephone-style handset

The HS-6 Telephone-style handset includes a wall/console mount hanger and push-to-talk switch. 1.8m/ 6ft coil with 4 pin female XLR connector.



PT-7



HS-6

Gooseneck Mics

GM-9 / GM-18

The GM-9 and GM-18 Gooseneck microphones features a gold-plated and threaded 6.35mm/0.25" Jack Connector and are available in 230mm/9" or 450mm/18" lengths. Each one is mounted on a durable, flexible gooseneck - including a fitted windscreen.

The uni-directional electret condenser microphone element have side and rear rejection of greater than 6db between 100Hz and 10kHz.

GN-250

The GN-250 is a 250mm/10" length Gooseneck microphone with a gold plated and threaded, 6.35mm/0.25" Jack Connector. Supplied with a fitted windscreen.

GN-450

The GN-450 is a 140mm/18" length Gooseneck microphone with a gold plated and threaded, 6.35mm/0.25" Jack Connector. Supplied with a fitted windscreen.

110/xxx Range (110/100, 110/340, 110/490)

The 110 range of Gooseneck Condenser microphones that offer excellent frequency response and audio sensitivity. The flexible and durable design is ideal for everyday use in both busy broadcast and live environments.

This range of microphones come supplied with a threaded 3 pin DIN (M) connectors and fitted windscreen.

The 110 range is available in three sizes:

110/100	100mm/3.9"
110/340	340mm/13.4"
110/490	490mm/19.3"

110/340/DIR

The Gooseneck (340mm/13.4") Directional microphone is designed to increase voice pick-up and reduce background noise.

110/340/NC

The Gooseneck (340mm/13.4") Noise Cancel microphone ensures increased noise cancellation. The 110/340/NC is designed for use in the most challenging environments such as sports arenas and live entertainment venues.



GM-9 / GM-18



GN-250 / GN-450



**110/100
(enlarged image)**



110/340 / 110/340/DIR / 110/340/NC



110/490

Panel Compatibility Chart for Headsets

Headset	Connector type	V-Series (X4)	V-Series (X5)	FreeSpeak CellCom	BPS2202	RS-601/602/603	RS-603R	RS-623R	RS-622/623	Encore & PL Pro	ICS Panels	I-Series	4000 Series (XLR 4)	4000 Series (XLR 5)	4000 Series (DIN 5)
CC25	2.5mm Jack (M)					✓	✓	✓	✓						
CC-26K-DIN	DIN 5 (M)				✓										✓
PT-7	XLR 4 (F)	✓		✓		✓				✓	✓	✓	✓		
HS-6	XLR 4 (F)	✓		✓		✓				✓	✓	✓	✓		
CC-95	XLR 4 (F)	✓		✓		✓				✓	✓	✓	✓		
CC-60	XLR 4 (F)	✓		✓		✓				✓	✓	✓	✓		
CC-40	XLR 4 (F)	✓		✓		✓				✓	✓	✓	✓		
CC-260	XLR 4 (F)	✓		✓		✓				✓	✓	✓	✓		
CC-27	XLR 4 (F)	✓		✓		✓				✓	✓	✓	✓		
CC-26	XLR 4 (F)	✓		✓		✓				✓	✓	✓	✓		
CC-26K-X4	XLR 4 (F)	✓		✓		✓				✓	✓	✓	✓		
CC-95-R	XLR 4 (M)						✓								
CC-260-R	XLR 4 (M)						✓								
CC-26K-X5	XLR 5 (M)		✓					✓							✓
CC-95-X5	XLR 5 (M)		✓					✓							✓
CC-260-X5	XLR 5 (M)		✓					✓							✓
CC-260-6	XLR 6 (F)								✓						

Panel Compatibility Chart for Microphones

Headset	Connector type	V-Series	Encore & PL Pro	ICS Panels Series	I-Series	4000
GM-9	1/4 inch Jack Screw (M)		✓	✓	✓	
GM-18	1/4 inch Jack Screw (M)		✓	✓	✓	
GN-250	1/4 inch Jack Screw (M)		✓	✓	✓	
GN-450	1/4 inch Jack Screw (M)		✓	✓	✓	
110-100	3 Pin DIN Screw Lock (M)	✓				✓
110-340	3 Pin DIN Screw Lock (M)	✓				✓
110-340/DIR	3 Pin DIN Screw Lock (M)	✓				✓
110-340/NC	3 Pin DIN Screw Lock (M)	✓				✓
110-490	3 pin DIN Screw Lock (M)	✓				✓