

2510 Controller SPECIFICATIONS

Description

- The 2510 is a playback controller that can output control signals to 512 DMX channels (or 31 Martin protocol fixtures). Sequences and shows are programmed using the Martin LightJockey or 3032 controller and downloaded for playback with the 2510 via a standard serial port connection.
-

Physical

- Length: 483 mm (19 in.)
 - Width: 65 mm (2.6 in.)
 - Height: 89 mm (3.5 in.)
 - Weight: 1kg (2.2 lb)
 - Shipping dimensions (LxWxH): 580 x 260 x 150 mm (22.9 x 10.2 x 5.9 in.)
 - Shipping weight: 2 kg (4.4 lb)
-

Installation

- Rack mounting dimensions: 19 in./2U
-

AC Supply

- EU model: 220-240 V / 50-60 Hz
 - US model: 100-130 V / 50-60 Hz
-

Power Consumption

- 2.5 W
-

Control & Programming

- Number of 3032 Controller scenes: 8024
 - Number of LightJockey Controller scenes: from 247 @ 512 channels to 42,325 @ 1 channel
 - Triggers: Auto, Manual and Music (built-in microphone)
 - Display: Two-digit 20 x 25 mm LED
 - Blackout function
-

Connections

- Data input: RS-232 (may be used as RS-232 to Martin RS-485 converter) input
 - Data output: 3-pin XLR socket (wired for the Martin control protocol, adaptor required for DMX)
-

Included items

- User manual
 - Link cable: 5 meters (16 feet)
 - 120 ohm termination plug
-

Ordering information

- 2510 Controller (220-240 V): P/N 90716000
 - 2510 Controller (100-130 V): P/N 90716100
-