



## THE ARCHITECTURAL OUTLINE

**Gobostorm-Gobostorm Plus**

GR0466 575W  
GR0468 Plus 575W

## Gobo Projector

Designed as a further and more powerful development of the GOBOCLIP unit, GOBOSTORM is a fully weatherproofed (IP66) high power zoom gobo projector, able to project a bright and accurate rendition of any graphic design or logo.

Using a 575W discharge lamp with a high precision optical group, GOBOSTORM can project one image with high brightness and clarity. The high power lamp gives the ability to reach long distances or create enormous impact when used for closer projections. GOBOSTORM has on board DMX control or, alternatively, the unit can be controlled by an external DMX controller, to set the rotating image speed settings. The focus is manually set and the projection angle range can be extended by an optional zoom objective. This gives much flexibility with image size and projection distance. GOBOSTORM is designed for easy installation and programming, together with reliability even in the harshest weather conditions. This is a new opportunity for advertising, logo or image creation, together with colour, in any outdoor urban environment. More functions may be performed by GOBOSTORM PLUS, which shares all GOBOSTORM's basic features with the indexable rotatable gobo wheel, the eight colour wheel and special effects (three prisms and frost) to allow creativity with abstract or pattern images. Blackout, strobe and mechanical dimmer functions make this unit even more complete.

[Back to The Architectural Outline](#)

**Technical features****- LAMP SOURCE**

Type:	MSD (suggested), HSD, MSR, HSR (optional)
Wattage (W):	575
Base:	GX 9,5
Lamp life (h):	1000 (MSR-HSR), 3000 (MSD-HSD)
Lumens:	45.000 (MSR-HSR), 49.000 (MSD-HSD)

**- COLOURS**

Dichro filters:	1 (optional) - Gobostorm, 8 + White - Gobostorm Plus only
-----------------	---

**- PROJECTION**

Angle:	10°-24°(standard), 18°-32°(optional), 33°-42°(optional)
Focus:	Manual
Zoom:	Manual
Dimmer:	Mechanical (Gobostorm Plus only)

## FOCUS ON



## ASK FOR A QUOTATION



## VIEW LIST



## GALLERY



## DOWNLOAD



## Search

GO

Strobe:	9 Fps (Gobostorm Plus only)
Effects:	3-F Prism, 5-F Prism, Multiple Image (Gobostorm Plus only)
Filters:	1 (optional) - Gobostorm, Frost (Gobostorm Plus only)
Glass gobos:	1 (optional) - Gobostorm
Metal gobos:	1 (optional) - Gobostorm
Gobos Ø (mm):	1 metal or glass (D-Size Ext. 53.3, Int. 40.0), 5 metal provided as standard; dichroic gobos can also be mounted (D-Size Ext. 53.3, Int. 40.0)

#### - OPERATION

DMX channels:	1 (Gobostorm), 6 (Gobostorm Plus)
Stand alone:	✓
Master / Slave:	✓
On Board Control:	✓

#### - HOUSING

Weather protection:	IP66
Cooling:	FV (Gobostorm Plus only)

#### - SIZE (mm)

Height:	575, 185 (ballast)
Width:	510, 320 (ballast)
Depth:	545, 245 (ballast)

#### - - WEIGHT (kg)

Main fixture:	20 (Gobostorm), 24 (Gobostorm Plus)
Ballast set:	12

#### - POWER

Input (V):	230-240, 110 (optional)
HZ:	50-60
AMP:	3,5 (230-240), 8 (110)

 [Back to The Architectural Outline](#)



[Home Page](#)   [Company](#)   [Products](#)   [News](#)   [Contacts](#)   [Distributors](#)   [Merchandising](#)

**GRIVEN S.r.l.** - Via Bulgaria 16 - 46042 Castel Goffredo - Mantova - Italy  
Tel. +39.0376.779483 - Fax. +39.0376.779.682 - Email: [griven@griven.com](mailto:griven@griven.com)

- **DISCLAIMER** -