

Scroller Specifications

	SMART COLOR [®] 5.25	SMART COLOR [®] 7.25	SMART COLOR [®] 10
Fixture Compatibility	Ideal with narrow beam fixtures including Source 4 with a 19° barrel, Shakespeare with a 20° barrel, Strand SL with a 19° barrel, and Selecon with a 5-13° barrel.	Ideal with all ellipsoidals and many wash fixtures.	Ideal for 1-2K watt fixtures.
Design			
Dimensions	10 5/8" (H) x 9 5/8" (W) x 2 5/8" (D) 270mm (H) x 245mm (W) x 67mm (D)	13 1/2" (H) x 11 3/4" (W) x 2 5/8" (D) 343mm (H) x 298mm (W) x 67mm (D)	16 1/4" (H) x 14 1/2" (W) x 2 5/8" (D) 413mm (H) x 368mm (W) x 67mm (D)
Material/Color	Lightweight aluminum, black powder coat	Lightweight aluminum, black or white powder coat	Lightweight aluminum, black powder coat
Weight	3.6 lbs. (1.6 kg.)	4.6 lbs. (2.1 kg.)	5.6 lbs. (2.5 kg.)
Aperture	5.25" (133 mm)	7.25" (184mm)	10" (254mm)
Mounting Plate	6 1/4" x 6 1/4" (159mm x 159mm), included with scroller	10" x 10" (254mm x 254mm), 7 1/2" x 7 1/2" (190mm x 190mm), or 6 1/4" x 6 1/4" (159mm x 159mm), included with scroller; Universal mounting plate that adjust between 5 3/4" - 10" (146mm-254mm) to fit all ellipsoidal and many wash fixtures available for additional upcharge	10" x 10" (254mm x 254mm), included with scroller
Ports	4-pin XLR ports on back of unit for easy access and daisy chain capability	4-pin XLR ports on back of unit for easy access and daisy chain capability	4-pin XLR ports on back of unit for easy access and daisy chain capability
Heat Deflectors	Two internal deflectors plus Apollo Gel Shield	Two internal deflectors plus Apollo Gel Shield	Two internal deflectors plus Apollo Gel Shield
Safety Cable	Yes	Yes	Yes
Operational			
Gel String Capacity	2-16 frames	2-16 frames	2-11 frames
Gel String Loading	Auto/manual load	Auto/manual load	Auto/manual load
Cooling System	Variable speed, single fan with local or remote speed control	Variable speed, single fan with local or remote speed control	Variable speed, dual fan with local or remote speed control
Scroll Speed Auto Scroll Continuous /Frame By Frame	Variable 19 - 30 sec. / Variable 19 - 30 sec.	Variable 19 - 30 sec. / Variable 19 - 30 sec.	Variable 19 - 30 sec. / Variable 19 - 30 sec.
Max. Speed	High speed: 2.0 sec. head to tail with 16 frames	High speed: 2.0 sec. head to tail with 16 frames	High speed: 2.0 sec. head to tail with 11 frames
Address	Rotary dip switch up to address 512	Rotary dip switch up to address 512	Rotary dip switch up to address 512
Power Requirement	24VDC	24VDC	24VDC
Power Consumption	0.9 AMPS @ 24VDC (fan & speed high); 0.7 AMPS @ 24VDC (fan & speed low)	0.9 AMPS @ 24VDC (fan & speed high); 0.7 AMPS @ 24VDC (fan & speed low)	0.9 AMPS @ 24VDC (fan & speed high); 0.7 AMPS @ 24VDC (fan & speed low)
DMX Channels Required	One (two if using remote fan control)	One (two if using remote fan control)	One (two if using remote fan control)
Protocol Requirements	DMX 512 (1990)	DMX 512 (1990)	DMX 512 (1990)
Input Connector	XLR 4-pin male (power and control protocol)	XLR 4-pin male (power and control protocol)	XLR 4-pin male (power and control protocol)
Output Connector	XLR 4-pin female (power and control protocol)	XLR 4-pin female (power and control protocol)	XLR 4-pin female (power and control protocol)
LED Indicators	Red - power signal; Green - DMX signal/warning signal	Red - power signal; Green - DMX signal/warning signal	Red - power signal; Green - DMX signal/warning signal

Gel String Information For Smart Color[®] 5.25, Smart Color[®] 7.25, And Smart Color[®] 10.



Apollo Standard Rock 'n Roll Gel Strings

consist of clear and...

6400 Pilsner Yellow	8750 Hot Pink	4250 Apollo Blue
7600 Apollo Orange	3150 Sour Grape	* 4200 Bright Blue
7450 Golden Amber	* 3700 Groovy Grape	* 4950 Caribbean Blue
8300 Diva Red	* 3900 Voodoo Lavender	* 5500 Neptune Blue Green
8350 Bludgeon Red	4450 Heavenly Blue	5400 Rock 'n Roll Green

* This color not included in Smart Color[™] 10 standard gel string.

Apollo Standard Theater Gel Strings

consist of clear and...

6300 Neon Yellow	8250 Vixen Red	4800 Ice Blue
7150 Santa Fe Amber	8450 Spanked Pink	4450 Heavenly Blue
7650 Coral Amber	8750 Hot Pink	* 4400 After Hours Blue
7550 Spiced Rum Amber	3250 Dominant Lavender	* 5960 Margarita Green
* 7600 Apollo Orange	* 3700 Groovy Grape	* 5500 Neptune Blue Green

* This color not included in Smart Color[™] 10 standard gel string.

Custom Gel Strings

Available using Apollo, Rosco, GAM or Lee gel. Allow 4-5 days.

4130 Fourier Drive, Fort Wayne, IN 46818 USA

U.S. PHONE: +1.260.497.9191

FAX: +1.260.497.9192

www.internetapollo.com

01/07