



CHROMA KEY

MSDS No.:5710, 5711

MSDS Preparation Date: January 3, 2007

Page 1 of 6

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name : **CHROMA KEY**
 Chroma Key Blue (No. 5710)
 Chroma Key Green (No. 5711)

Product Use : Paint

Chemical Family : Mixture

Supplier's name and address:
Rosco Laboratories Inc.
 52 Harbor View Avenue
 Stamford, CT, United States
 06902

24 Hr. Emergency Tel # : (800) 424-9300

HMIS Rating : * - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: * 1 *Flammability:* 0 *Reactivity:* 0

WHMIS Classes:



TOXIC

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>% (weight)</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
			<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Chroma Key Blue						
No hazardous ingredients	N/A-v	N/Av	N/Av	N/Av	N/Av	N/Av
Chroma Key Green						
Propylene glycol	57-55-6	1.0 - 5.0	N/Av	N/Av	N/Av	N/Av

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Blue liquid. (Chroma Key Blue); Green liquid. (Chroma Key Green). Slight odor. May cause skin and eye irritation. May cause skin sensitization.

POTENTIAL HEALTH EFFECTS

Target organs : None reported by the manufacturer.

Routes of exposure : *Inhalation:* YES *Skin Absorption:* YES *Skin & Eyes:* YES *Ingestion:* YES

Potential acute health effects :

Eyes: Causes eye irritation. May cause conjunctivitis, irritation, and inflammation of mucous membranes. May cause burning sensation, redness and tearing (watering).

Skin: Irritating to skin. Possible irritation, defatting or dermatitis (rash). Components of the product may be absorbed into the body through the skin. May cause central nervous system depression.



CHROMA KEY

MSDS No.:5710, 5711

MSDS Preparation Date: January 3, 2007

Page 2 of 6

- Inhalation:* Can cause irritation of the respiratory tract. Prolonged exposure to vapors may be harmful to health. If higher concentrations are inhaled, additional symptoms may include coughing, shortness of breath, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.
- Ingestion:* This product may be aspirated (inhaled) into the lungs during ingestion. May cause mucous membrane irritation. Ingestion may cause symptoms similar to inhalation. May cause gastrointestinal irritation. Gastrointestinal irritation may include abdominal pain, nausea, diarrhea and vomiting.

Potential chronic health effects

- : Prolonged skin contact may defat the skin and produce dermatitis.

Medical conditions aggravated by overexposure

- : None expected, when used as intended.

Additional health hazards

- : None reported by the manufacturer.

Potential environmental effects

- : None reported by the manufacturer.

SECTION 4 - FIRST AID MEASURES

- Inhalation** : If breathed in, move person into fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.
- Skin contact** : Flush with plenty of water. Wash off with soap and plenty of water. Remove and wash contaminated clothing before re-use. If irritation persists, seek prompt medical attention.
- Eye contact** : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If irritation persists, seek prompt medical attention.
- Ingestion** : Call a physician or Poison Control Centre immediately. Do NOT induce vomiting. Guard against aspiration into lungs by having the individual turn on their left side.
- Notes For Physician** : Treat symptomatically.

SECTION 5 - FIRE FIGHTING MEASURES

Fire hazards/conditions of flammability

- : Not flammable under normal conditions of handling. This product will not burn, due to its water content.

Flammability classification (OSHA 29 CFR 1910.1200)

- : Combustible Liquid Class III B.

Flash point

- : Not applicable.

Flash point Method

- : Not applicable.

Auto-ignition temperature : Not available.

Lower flammable limit (% by vol.)

- : Not applicable.

Upper flammable limit (% by vol.)

- : Not applicable.

Suitable extinguishing media

- : Dry chemical, foam, carbon dioxide and water fog.

Explosion data: Sensitivity to mechanical impact / static discharge

- : Not expected to be sensitive to mechanical impact or static discharge.

Special fire-fighting procedures/equipment

- : Firefighters should wear an approved full-face, self-contained breathing apparatus (SCBA) and impervious clothing. Water may be ineffective on fire, but may be helpful in cooling unburned containers. Do not use a solid water stream as it may scatter and spread fire. If water is used, fog nozzles are preferable.

Hazardous combustion products

- : Carbon dioxide and carbon monoxide.

Oxidizing properties

- : None reported by the manufacturer.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

- Personal precautions** : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Avoid breathing vapors. Wear resistant clothing and boots.
- Environmental precautions** : Prevent product from entering drains, sewers, waterways and soil.



CHROMA KEY

MSDS No.:5710, 5711

MSDS Preparation Date: January 3, 2007

Page 3 of 6

- Spill response/cleanup** : Eliminate all ignition sources if safe to do so. Ventilate area of release. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13).
- Containment** : Should not be released into the environment. Recover free liquid or cover with inert absorbent material and place into appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

- Safe Handling procedures** : Use with adequate ventilation. Avoid breathing vapor or mist. Avoid contact with skin and eyes. Wash hands thoroughly after using this product, and before eating, drinking or smoking. Do not re-use empty containers. Do not puncture container. Keep in properly labeled containers. Wear suitable protective equipment. Do not ingest.
- Storage requirements** : Store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks and other possible sources of ignition. Do not freeze. Keep container tightly closed when not in use. Store in upright position only. Keep out of the reach of children. Empty product containers may contain hazardous product residue.
- Incompatible materials** : Peroxides and/or strong oxidizing agents.
- Special packaging materials** : Liquid-proof glass, plastic or non-corrodible metal containers are recommended.

SECTION 8 - EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Ventilation and engineering measures** : Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Use explosion-proof equipment. Use non-sparking equipment. Discharge exhaust only in area away from ignition sources.
- Respiratory protection** : Use NIOSH/MSHA approved full-face respirator with an organic vapor cartridge if the recommended exposure limit is exceeded. In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.
- Skin protection** : Wear impervious gloves, such as neoprene or nitrile rubber.
- Eye / face protection** : Safety glasses with side-shields or chemical splash goggles.
- Other protective equipment** : Emergency showers and eyewash facilities should be nearby. Depending on conditions of use, safety shoes and additional protective clothing may also be necessary.
- General hygiene considerations** : Wash hands thoroughly after using this product, and before eating, drinking or smoking. Wash hands before breaks and at the end of workday.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- | | | | |
|--|---|---|--|
| Physical state | : Liquid. | Appearance | : Blue liquid. (Chroma Key Blue)
Green liquid. (Chroma Key Green) |
| Odor | : Slight odor. | Odor threshold | : Not available. |
| pH | : Not available. | | |
| Boiling point | : 100 °C (Chroma Key Blue)
187.2 °C (Chroma Key Green) | Specific gravity | : 1.4 (Chroma Key Blue)
1.3 (Chroma Key Green) |
| Melting/Freezing point | : Not available. | Coefficient of water/oil distribution | : Not available. |
| Vapor pressure (mmHg @ 20° C / 68° F) | : 1.0 - 760 (Chroma Key Blue)
0.06 -760 (Chroma Key Green) | Solubility in water | : Soluble. |
| Vapor density (Air = 1) | : Heavier than air. | Evaporation rate (n-Butyl acetate = 1) | |



CHROMA KEY

MSDS No.:5710, 5711

MSDS Preparation Date: January 3, 2007

Page 5 of 6

SECTION 14 - TRANSPORTATION INFORMATION

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
TDG	None	Not regulated.	Not regulated	-None-	
TDG Additional information	None.				
49CFR/DOT	None	Not regulated.	Not regulated	-None-	
49CFR/DOT Additional information	None.				
ICAO/IATA	None	Not regulated.	Not regulated	-None-	
ICAO/IATA Additional information	None.				
IMDG	None	Not regulated.	Not regulated	-None-	
IMDG Additional information	None.				

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

All ingredients are listed on the TSCA Inventory, or are exempted materials.

SARA Section 313: This material is not subject to SARA notification requirements, since it does not contain any Toxic Chemical Constituents above de minimus concentrations.

US State Right to Know Laws:

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

Canadian Regulations:

Canadian Environmental Protection Act (CEPA): All ingredients are listed on the DSL, or are exempted materials.
 Canadian WHMIS Classification: D2B.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16 - OTHER INFORMATION

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- IARC: International Agency for Research on Cancer
- N/Ap: not applicable
- N/Av: not available
- NIOSH: National Institute of Occupational Safety and Health
- NTP: National Toxicology Program
- OSHA: Occupational Safety and Health Administration



Rosco Laboratories Inc.
 52 Harbor View Avenue
 Stamford, CT, USA, 06902
 Phone: (203) 708 8900



CHROMA KEY

MSDS No.:5710, 5711

MSDS Preparation Date: January 3, 2007

Page 6 of 6

References : Information obtained from sources including original supplier's Material Safety Data Sheet, and references including RTECS and CCOHS Cheminfo.

<p>Prepared for: Rosco Laboratories Inc. 52 Harbor View Avenue Stamford, CT, USA, 06902 Phone: (203) 708 8900 http://http://www.rosco.com/</p>	
<p>Prepared by: ICC The Compliance Center Inc. Canada: 1-888-977-4834 USA: 1-888-442-9628 http://www.thecompliancecenter.com</p>	

DISCLAIMER OF LIABILITY

Every effort has been made to ensure that the safety information on this sheet is accurate, but because Rosco Laboratories, Inc. has no control over the conditions under which the product will be used, liability is limited exclusively to replacement or refund of the purchase price of this product. Except as stated herein, there are no express or implied warranties, including implied warranties of merchantability or fitness for a particular purpose. Rosco Laboratories, Inc. assumes no liability for injury or incidental or consequential damages arising out of storage, handling or use of this product.

Preparation Date: January 3, 2007

END OF DOCUMENT