

Froggy's Fog
302 Rutherford Lane
Columbia, TN 38401
615.469.4906
sales@froggyfogs.com

CONTENTS

1 BEFORE YOU BEGIN 1

1.1 What Is Included 1

1.2 Unpacking Instructions 1

1.3 Symbols..... 1

1.4 Disclaimer 1

1.5 Safety Notes..... 1

 1.5.1 Personal Safety.....1

 1.5.2 Mounting and Rigging1

 1.5.3 Power and Wiring.....2

 1.5.4 Operation.....2

2 INTRODUCTION..... 2

2.1 Description 2

2.2 Features..... 3

3 TECHNICAL SPECIFICATIONS..... 3

4 SETUP 3

4.1 AC Power 3

4.2 AC Plug 4

4.3 Mounting 4

 4.3.1 Orientation4

 4.3.2 Rigging4

5 OPERATION..... 4

5.1 Preparing for Operation..... 4

5.2 On-device Control Mode & Operation 4

5.3 Timer Remote Control Mode & Operation 5

 5.3.1 Timer Mode.....5

 5.3.2 Continuous Mode5

 5.3.3 Manual Mode5

5.4 Wireless Remote-Control Mode & Operation (Optional) 6

5.5 Fluid Sensor..... 6

6 TECHNICAL INFORMATION..... 6

6.1 Maintenance 6

6.2 Storage 7

 6.2.1 Machine Storage7

7 WARRANTY INFORMATION 7

 7.1.1.....7

1 BEFORE YOU BEGIN




1.1 What Is Included

- Machine
- Timer Remote Control
- Hanging Bracket
- Power Cord
- User Manual

1.2 Unpacking Instructions

Carefully unpack the product immediately and check the container to make sure all the parts are in the package and are in good condition. If the box or the contents (the product and included accessories) appear damaged from shipping, or show signs of mishandling, notify the carrier or dealer/seller immediately. In addition, keep the box and contents for inspection.

1.3 Symbols

Symbol	Meaning
	Caution Critical installation, configuration, or operation information. Not following these instructions may make the product not work, cause damage to the product, or cause harm to the operator.
	Important Important installation or configuration information. Failure to comply with this information may keep the product from working correctly.
	Information Useful information.

1.4 Disclaimer

The information and specifications contained in this User Manual are subject to change without notice. FROGGYS FOG assumes no responsibility or liability for any errors or omissions and reserves the right to revise or to create this manual at any time.

Copyright © 2018 FROGGYS FOG. All rights reserved.

1.5 Safety Notes

Please read the following Safety Notes carefully before working with the product. The notes include important safety information about installation, usage, and maintenance.

1.5.1 Personal Safety

- Always connect the product to a grounded circuit to avoid the risk of electrocution.
- During heating up and operation, the housing will be scalding hot. Do not touch.
- **The product is very hot during operation and it remains hot for a long time after operation has stopped. Do not touch the product' s nozzle.**
- Make sure that children, unauthorised people and animals do not obtain access to the machine.

1.5.2 Mounting and Rigging

- To prevent risk of fire or shock, do not expose the product to rain or moisture.

- CAUTION: When transferring product from extreme temperature environments, (e.g. cold truck to warm humid ballroom) condensation may form on the internal electronics of the product. To avoid causing a failure, allow product to fully acclimate to the surrounding environment before connecting it to power.
- Do not mount the product on a flammable surface (linoleum, carpet, wood, paper, carton, plastic, etc.).
- Do not use in a confined space. Always install the product in a location with adequate ventilation, at least 20 in (50 cm) from adjacent surfaces.
- When hanging this product, always secure to a fastening device using a safety cable.
- Be sure that no ventilation slots on the product's housing are blocked or clogged by dust. If necessary, remove the dust.

1.5.3 Power and Wiring

- Always make sure that the voltage of the outlet to which you are connecting the product is within the range stated on the decal or rear panel of the product.
- Make sure the power cord is not crimped or damaged.
- Never connect this product to a dimmer pack or rheostat.
- Never disconnect the product from power cord by pulling or tugging on the cord.
- To eliminate unnecessary wear and improve its lifespan, during periods of non-use completely disconnect the product from power via breaker or by unplugging it

1.5.4 Operation

- Do not operate this product if you see damage to the housing or cables. Have the damaged parts replaced by an authorized technician at once.
- Do not use the product as a space heater.
- Make sure there are no flammable materials close to this product while it is operating.
- The maximum ambient temperature is 104 °F (40 °C). Do not operate the product at higher temperatures.
- **Do not cover the ventilation slots when operating to avoid internal overheating.**
- **Do not cover or plug the output nozzle during operation.**
- Wipe up any fluid accumulation immediately. Moisture – also fluid – can damage the electrical components.
- You may hear a loud popping sound during operation. This is normal.
- Never carry the product by the power cord or any moving part. Always use the handles of the machine.
- **Drain the tank before transporting the product.**
- Always disconnect the product from the power source before cleaning.
- In the event of a serious operating problem, stop using the product immediately.
- This product contains no user-serviceable parts. Any reference to servicing in this User Manual will only apply to properly trained, certified technicians. Do not open the housing or attempt any repairs which can lead to damage or malfunction.
- **Use only FROGGYS FOG Water Based Fog Fluid.**



Keep this User Manual for future use. If you sell the product, be sure that the purchaser receives this document.

2 INTRODUCTION

2.1 Description

The Titan 1200 is a powerful 1300W Fog Machine with over 20,000CFM. The efficient heater core increases run times, Quick Ready Fog Technology (QRFT) has you ready to fog in less than 10 seconds after full cycle and it is ready to fog, and Advanced Low Fluid Sensing shuts down the machine when you run out of fluid to protect the heater core.

2.2 Features

- 1300W
- 20,000 CFM
- Oversized Heater Core for increased run times
- Quick Ready Fog Technology (QRFT) - Less than 10 seconds after full cycle and it is ready to fog
- Advanced Low Fluid Sensing
- IEC 320 C13 Power Connection
- 3" Venturi Style Nozzle Connection
- Durable 5 Liter Fluid Tank
- Built-In Hanging Bracket
- Timer Control Included (Wireless Optional)
- Electronics Compartment to keep all fluid related components away from boards
- Removable Fluid Tank Bracket for tight install applications
- Rubberized Feet

3 TECHNICAL SPECIFICATIONS

AC Power	Input Voltage & Rate	120 V, 60 Hz
	Current Limiter Type	Fuse
	Current Limiter Specifications	250V/15A
	Total Power Consumption	1,300 W
Heating	Heat Up Time	4 Mins
Capacity	Fluid Tank Capacity	1.3 Gal
	Output Duration with Fluid Tank Full	60 min
Output	Adjustable Output	YES
	Max Output Volume	20,000 cfm
	Max Output Height	15 Ft
	Fluid Consumption (100% Output)	80 ml/min
	Maximum Continuous Duration (100% Output)	40+secs
	Continuous Output	@ 30% maximum output
Placement & Mounting	Horizontal	YES
	Inclined	YES
	Vertical	YES
	Hang Upside Down	N/A
	Rigging & Trussing	Hanging Bracket
Control	On-device Manual Control	Green Illuminated Fog Button
	Wireless Control	Optional FFM-RM-WR5 / RF 433MHz
	Wired Control	Included
Certification	CE	N/A
	RoHS	N/A
Consumable	Consumable	Water Based Fog Fluid
Weight & Dimensions	Net Weight	20 lbs
	Gross Weight	25.5 lbs
	Machine Dimensions	21.3 x 12 x 11.5 in
	Packing Dimensions	25.5 x 14.4 x 13.6 in

4 SETUP

4.1 AC Power

The machine has a fixed voltage power supply and can work with an input voltage of AC 120 V, 60 Hz, depending on the specific model.

To determine the product's power requirements (circuit breaker, power outlet, and wiring), use the current value listed on the label affixed to the product's back panel, or refer to the product's specifications chart. The listed current rating indicates the product's average current draw under normal conditions.



Always connect the product to a protected circuit (circuit breaker or fuse). Make sure the product has an appropriate electrical ground to avoid the risk of electrocution or fire.



Never connect the product to a rheostat (variable resistor) or dimmer circuit, even if the rheostat or dimmer channel serves only as a 0 to 100% switch.

4.2 AC Plug

The FFM-TITAN-1200 comes with a power input cord terminated with an IEC connector on one end and an US plug on the other.

Fuse Replacement

- Disconnect the product from power
- Wedge the tip of a flat-head screwdriver into the slot of the fuse holder.
- Pry the safety cap out of the housing
- Remove the blown fuse from the clip on the front of the safety cap and replace with a fuse of the exact same type and rating.
- Re-insert the fuse holder and reconnect power.



Disconnect the product from power before replacing the fuse.

4.3 Mounting

Before mounting the product, read and follow the safety recommendations indicated in the Safety Notes.

4.3.1 Orientation

Always mount this product in a safe position and make sure there is adequate room for ventilation, configuration, and maintenance.

4.3.2 Rigging

FROGGYS FOG recommends using the following general guidelines when mounting this product.

- Before deciding on a location for the product, make sure there is easy access to the product for maintenance and programming purposes.
- Make sure that the structure or surface onto which you are mounting the product can support the product's weight (see the Technical Specifications).
- When mounting the product on the floor, make sure that the product and cables are away from people and vehicles.

5 OPERATION

5.1 Preparing for Operation

To prepare the FFM-TITAN-1200 for operation, perform the following steps.

- After checking that all the parts are intact and complete, position the machine on a flat surface.
- Withdraw the fluid tank from its compartment and remove its cap.
- Verify that the two plastic hoses attached to the cap are in place and in good condition.
- Fill the tank with fog fluid and return the tank back to its compartment in the FFM-TITAN-1200.
- Make sure the plastic hose entering the FFM-TITAN-1200 from the fluid tank cap is not bent or kinked.
- Always connect the product to a grounded circuit. Before power on, make sure it is connected with the rated voltage.

5.2 On-device Control Mode & Operation

The machine can be operated manually.

- The machine will begin heating once the unit has been turned on.
- When the Green button is illuminated, the machine has come up to temperature.
- Press the illuminated button to trigger fog output.

5.3 Timer Remote Control Mode & Operation

The wired timer controller allows you to automatically trigger fog output by setting interval and duration times. LED indicator lights display the machine and controller's current state. Rotary knobs set interval time, output, and duration time, while manual and continuous buttons allow overriding control.

- Plug in the fog machine to power.
- Plug in the wired timer controller to the Manual Remote Connector socket on the back of the fog machine. (See the product Overview.)
- Allow the FFM-TITAN-1200 4 minutes to heat up before continuing. (See Fluid Tank Indicator Lights.)

The wired timer controller has three modes of operation: timer, continuous, and manual.

5.3.1 Timer Mode

To trigger the machine with the timer function, follow the instructions below:

- Set the desired output level with the OUTPUT knob.
- Set the INTERVAL and DURATION knobs to the desired positions.
 - The INTERVAL knob sets the amount of time in between bursts of fog.
The DURATION knob sets the length of time that the fog machine will run during the burst.
- Press the <TIMER ON/OFF> latching button. The LED indicator above the button will light up. The timer will now run as set by the INTERVAL, DURATION, and OUTPUT knobs.
- Press the <TIMER ON/OFF> button again to turn off the timer.



- Set the INTERVAL and DURATION knobs to the desired positions.
 - The INTERVAL knob sets the amount of time in between bursts of fog.

The DURATION knob sets the length of time that the fog machine will run during the burst.



The <MANUAL> button will override the timer.

5.3.2 Continuous Mode

To trigger the machine to continuously cycle fog, follow the instructions below:

- Set the desired output level with the OUTPUT knob.
- Press the <CONTINUOUS> latching button. The LED indicator above the button will light up. The fog machine outputs fog until the <CONTINUOUS> button is pressed again.
- Press the <CONTINUOUS> button again to stop the fog output.



In order for Continuous mode to run uninterrupted, without the machine stopping to reheat, set the OUTPUT knob no higher than 30%. At Output levels above 30%, the fogger will cycle through intermittent bursts of fog during its reheating program.



**The duration of Continuous fog output is based on the capacity of the tank.
Fluid consumption will be significantly increased during Continuous mode.**

5.3.3 Manual Mode

To trigger the machine manually, do the following:

- Set the desired output level with the OUTPUT knob.
- Press and hold the <MANUAL> button on the wired timer controller. The LED indicator above the button will light up. The fog machine will output fog for as long as you hold down the <MANUAL> button.
- Release the <MANUAL> button to stop the fog output.



The duration of manual fog at any given output setting is based on the capability of the fog machine.

5.4 Wireless Remote-Control Mode & Operation (Optional)

The FFM-TITAN-1500-DMX allows for the optional wireless remote receiver to plug into the remote port on the fog machine. The fog output can be activated by pressing the "On" button on the remote and deactivated by pressing the "Off" button.

5.5 Fluid Sensor

This machine uses software-based fluid sensor to detect whether there is fluid inside the tube so as to protect the pump from being damaged.

- Fog output will be paused when fluid absence is detected.
- To restore operation, refill the tank, then press and hold the green fog button until the unit resumes producing fog.

6 TECHNICAL INFORMATION

6.1 Maintenance

Do not allow the FFM-TITAN-1200 to become clogged. Please follow these instructions for safely cleaning your fog machine if output become noticeably decreased. High Quality fluid recommended by the manufacturer lengthens the amount of time between periods of maintenance as described below.

Tools: Clean lint free cloth, coffee filter or similar fine mesh filter cloth, plastic or glass container larger than the reservoir size (do not use metal), distilled water and Froggys Fog fluid.

1. Allow the machine to cool down before handling.
2. Drain any Fog solution that remains in the tank into a container through the filter mesh for reuse.
3. Add distilled water to fill the Fog fluid reservoir approximately 1/3.
4. Run machine for 10 minutes. Fog will come out the first few cycles, followed by distilled water vapor.
5. Turn off the machine and allow to cool down, then drain the distilled water from the reservoir.
6. Refill the reservoir approximately 1/3 with good quality fog solution.
7. Turn the machine on, run for 10-15 minutes. Water vapor steam will come out the first few cycles, followed by fog. Continue cycling the machine for 5-10 fog cycles.
8. Turn off the machine and allow to cool, then wipe machine clean with clean lint free cloth.
9. The excess fog fluid is best stored in a sealable container. The solution in the tubing acts a lubricant and conditioner for the plastic and rubber parts in the fluid pump.
10. Store the machine in a cool, dry place when not in use. Avoid freezing temperatures and high heat. above 120 degrees and humid/damp locations which may cause control board failure.
11. If possible, remove from storage after 6 months and operate the machine for 15 minutes or more, then repeat step 8 – 10.



Test-run your FROGGYS FOG® FFM-TITAN-1200 on a monthly basis to achieve the best performance.

6.2 Storage

6.2.1 Machine Storage

Before storing the machine, clean it as described in the cleaning procedure above; however, only follow steps 1 through 5. Do not refill the tank with fog fluid if storing the machine. Cleaning the system prior to storage will help prevent any particles from condensing inside the pump or heater while not in use.

7 WARRANTY INFORMATION

7.1.1

Save these instructions. 2 Year Limited Warranty: Valid from the date of purchase. Warranty covers manufacturing defects only and does not cover misuse or abuse of the machine. Serial number, place of purchase with dated valid receipt must be submitted at time of service. Warranty is only valid with-in the United States. Buyer may be responsible for shipping fees associated with repairs.